Lo-OmniRidge

Lomanco™

Lomanco's LOR9-4 Lo-OmniRidge Shingle Over Specifications

Net Free Area	Color	Size	Roof Pitch	Packaging
11 Sq. Inches Per Linear Foot	Black	4 Foot	Any Up To 16/12	10 Per Box

LOR9-4 Features:

- Optional Pneumatic Nail Gun or Hammer Installed.
- Internal Aerodynamic Curved Baffles.
- External Perpendicular Omni Baffles.
- Weatherproof Underlapping Joint.
- Four Drain Holes per Foot per Side.
- 11" Net Free Area per Linear Foot.
- External Venturi Baffle.
- Pre-formed to 3/12 Pitch.
- Nail Holes Marked Every 6 inches - Supported Every Foot.
- Molded Nail Lines.
- Molded Centerline for Fast and Easy Alignment.
- Alignment Tabs.
- External Water Shield.
- Slot Width Guide Lines.
- Patented Molded-in Fanfolded Endplug Fits All Roof Pitches.

LOR9-4 Ventilation Guide

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
Required Length(feet)	22	33	44	55	66	77
Intake Required(in^2)	242	363	484	605	726	847



LO449